

OutWrite 1.4



MODULE SPECIFICATION

Kernal Technology
Infrared technology

Sensor Accuracy
+/- 6 pixels

Throw Ratio
1.4

Screen Size
Up to 120" diagonal

Installation
Up to 30 degree vertical angle

Power Consumption
<0.5w (Power from USB interface)

SYSTEM REQUIREMENT

OS Required
Microsoft Windows XP (SP2) / Vista / Windows 7

Processor Type
Intel Core Duo or above

RAM Size
512MB or above

Minimum HHD Space
30MB

Hardware Interface
USB Port

PACKING INFORMATION

Dimensions (WxHxD)
4.3" x 0.8" x 3.1" / 110 x 20 x 80 mm

Net Weight
0.2 lbs / 80g

Packaged Dimensions (W x H x D)
16.9" x 2.8" x 5.9" / 430 x 70 x 150 mm

Packaged Net Weight
1.6 lbs / 740g

Included Standard Accessories
Light Baton (AA Batteries x 2)
USB cable mini (5P/A x 1.5m)
Installation hardware x 1 set
Quick Start Guide (Universal)
CD (User manual, Interactive software - LightPenII)
Light Pen (AAA Batteries x 3)

Optional Accessories
USB Extender

REGULATIONS

Regulations
FCC, CE

The BOXLIGHT OutWrite is a stand-alone interactive module. Once installed, the OutWrite gives any projector interactive capabilities. Simply calibrate the camera module with your projector, install the LightPenII software, and begin interacting.