

SOLID SHINE LCD Boosts Image Brightness While Reducing Your Workload, Delivering an Effortless Learning Experience



White Models



Black Models

* Lens sold separately.



PT-MZ16K Series			
	PT-MZ16KL	PT-MZ13KL	PT-MZ10KL
Light Output	16,000 lm	13,000 lm	10,000 lm
Resolution	WUXGA		

• Pure Color, High Brightness, and Long-Life Operation

At up to 16,000 lm*¹, color erupts in WUXGA. Radiant pictures are achieved with new 15.4 mm (1") LCD panels, Triple Laser Engine, 4K/60p signal input*², and refined cooling system.

• Unbeatable Reliability in the Real-World Conditions

To quickly fix problems while maintaining image display, the projectors feature Panasonic's new Triple Laser Engine with failover circuitry, a secondary backup signal input, and Information Monitor to show error information.

• Compact, Flexible, and Ready for a Stress-free Install

Easy-to-handle compact body weighs under 22.3 kg*³ (49.2 lbs.), runs at just 38 dB*⁴, and suits seven optional zoom lenses for flexible installation. Setup is expedited with Geo Pro software*⁵.

Specifications (Tentative)

Model	PT-MZ16KL	PT-MZ13KL	PT-MZ10KL
Projector type	LCD projectors		
LCD panel	Panel size	25.4 mm (1.0 in) diagonal (16:10 aspect ratio)	
	Display method	Transparent LCD panel (x 3, R/G/B)	
	Drive method	Active matrix method	
	Pixels	2,304,000 (1920 x 1200) pixels x 3, total of 6,912,000 pixels	
Light source	Laser diodes		
Light output*1	16,000 lm	13,000 lm	10,000 lm
Time until light output declines to 50 %*2	20,000 hours (NORMAL)/24,000 hours (ECO)		
Resolution	1920 x 1200 pixels		
Contrast ratio*1	3,000,000:1 (Full On/Full Off)		
Screen size [diagonal]	1.78–25.4 m (70–1,000 in), 16:10 aspect ratio		
Center-to-corner zone ratio*1	90 %		
Lens	Optional powered zoom lenses		
Lens shift	Vertical: TBD, Horizontal: TBD		
Keystone correction range	Vertical: ±40°, Horizontal: ±15°		
Keystone correction range with optional ET-UK20 Upgrade Kit	Vertical: ±40°, Horizontal: ±40°		
Installation	Ceiling/floor, front/rear, free 360-degree installation		
Terminals	SDI IN	BNC x 1: 3G/HD/SD-SDI input	
	HDMI IN	HDMI 19-pin x 1 (Compatible with HDCP, Deep Color, 4K/60p signal input)	
	DVI-D IN	DVI-D 24-pin x 1 (DVI 1.0 compliant, compatible with HDCP, compatible with single link only)	
	RGB IN	D-sub HD 15-pin (female) x 1 (RGB/YPbPr/YCbCr)	
	SERIAL IN	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)	
	SERIAL OUT	D-sub 9-pin (male) x 1 for link control	
	REMOTE 1 IN	M3 x 1 for wired remote control	
	REMOTE 1 OUT	M3 stereo mini-jack x 1	
	REMOTE 2 IN	D-sub 9-pin (female) x 1 for external control (parallel)	
	DIGITAL LINK/LAN	RJ-45 x 1 for network and DIGITAL LINK connection (HDBaseT™ compliant), 100Base-TX (Compatible with PjLink™ [Class 2], Art-Net, HDCP, Deep Color, 4K/60p signal input)	
	LAN	RJ-45 x 1 for network connection, 10Base-T, 100Base-TX (Compatible with PjLink™ [Class 2], Art-Net)	
	USB	USB Connector (Type A) x 1 (Output 5 V/2 A)	
	Power supply	AC 100–240 V, 50/60 Hz	
Power consumption	TBD		
Cabinet materials	Molded plastic		
Filter	Included (Estimated maintenance time: approx. 20,000 hours)		
Operation noise*1	38 dB/TBD/TBD (NORMAL/ECO/QUIET) (TBD)	35 dB/TBD/TBD (NORMAL/ECO/QUIET) (TBD)	35 dB/TBD/TBD (NORMAL/ECO/QUIET) (TBD)
Dimensions (W × H × D)	650 x 185*3 x 440 mm (25 19/32" x 7 9/32" x 17 5/16") (Without lens) (Not including protruding parts)		
Weight*4	Approx. 22.3 kg (49.2 lbs) (TBD)		
Operating environment	Operating temperature: 0–45 °C (32–113 °F)*5; Operating humidity: 10–80 % (no condensation)		
Applicable software	Logo Transfer Software, Multi Monitoring & Control Software, Early Warning Software, Geometry Manager Pro, Smart Projector Control for iOS/Android™		

*1 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2012 international standards. Value is average of all products when shipped. *2 Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast contents, NORMAL Mode, Dynamic Contrast [2], under conditions with 30 °C (86 °F), 700 m (2,297 ft) above sea level, and 0.15 mg/m³ of particulate matter. Estimated time until light output declines to 50 % varies depending on environment. *3 With legs at shortest position. *4 Average value. May differ depending on the actual unit. *5 Light output is limited at operating temperatures higher than 30 °C (86 °F), and projectors cannot be operated at altitudes higher than 2,700 m (8,858 ft) above sea level.

Optional Accessories

- **Zoom Lens**
ET-EMW200 (0.48-0.55) / ET-EMW300 (0.55-0.69) / ET-EMW400 (0.69-0.95) / ET-EMW500 (0.95-1.35) / ET-EMS600 (1.35-2.11) / ET-EMT700 (2.11-4.14) / ET-EMT800 (4.14-7.44)
- **Ceiling Mount Bracket**
ET-PKD120H (for high ceilings) / ET-PKD120S (for low ceilings) / ET-PKD130H (TBD)
- **Replacement Filter**
ET-RMF100
- **Attachment for Ceiling Mount Bracket**
ET-PKE301B
- **DIGITAL LINK Switcher**
ET-YFB200G
Note: ET-YFB200G is not compatible with 4K signals.
- **Digital Interface Box**
ET-YFB100G
Note: ET-YFB100G is not compatible with 4K signals.
- **Geometry Manager Pro Software Upgrade Kit**
ET-UK20
- **Auto Screen Adjustment Upgrade Kit**
ET-CUK10/ET-CUK10P
- **Early Warning Software**
ET-SWA100 Series
Note: Part number suffix may differ depending on the license type.
* Multi Monitoring & Control Software Ver. 2.0 or later is required. Please download from the following website: <https://panasonic.net/cns/projector/download/application/>

Panasonic®

Weights and dimensions shown are approximate. Specifications and appearance are subject to change without notice. Product availability may vary by country or region. This product may be subject to export control regulations. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries. Trademark PjLink is a trademark applied for trademark rights in Japan, the United States of America and other countries and areas. Android is a trademark or registered trademark of Google LLC. IOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license. SOLID SHINE is a trademark of Panasonic Corporation. All other trademarks are the property of their respective trademark owners. © 2019 Panasonic Corporation. All rights reserved.



For more information about Panasonic projectors, please visit:
Projector Global Website – panasonic.net/cns/projector
Facebook – www.facebook.com/panasonicprojectoranddisplay
YouTube – www.youtube.com/user/PanasonicProjector

All information included here is valid as of June 2019.

PT-MZ16KPRE2 Printed in Japan.