

PT-RCQ10 Series

1-Chip DLP™ Projectors

AVAILABLE FROM NOVEMBER 2019

Detailed, Color-Rich Images and Seamless Integration Help You Create Immersive Environments



Black Models



White Models



PT-RCQ10 Series				
	PT-RCQ10	PT-RCQ10L	PT-RCQ80	PT-RCQ80L
Light Output	10,000 lm*1		8,000 lm*1	
Resolution	4,608,000 pixels / 2715 x 1697 dots (With Smooth Pixel Drive: ON)			
Lens	With supplied lens	Without lens	With supplied lens	Without lens

*Smooth Pixel Drive is a technology that shifts the pixel diagonally by 0.5 pixels to create a 2715 x 1697 high-resolution image.

• Detailed Images Rich in Natural Colors

Newly developed Rich Color Harmonizer achieves deeper, more vibrant color expression. Combined with Smooth Pixel Drive, a technology that creates crisp yet smooth images using 1-axis wobbling, you can enjoy colorful and highly detailed images beyond the panel resolution.

• Seamless Integration with SLOT NX and Full Lens Lineup

With technologies to support 4K playback, including 4K signal input via HDMI®, DIGITAL LINK, and optional SLOT NX interface boards, the seamless integration of 4K content is greatly simplified. Compatibility with our 1-Chip DLP™ lenses, including the ET-DLE020 Ultra-Short-Throw Zoom Lens, further enhances application flexibility.

• Excellent Reliability in Tough Conditions

Further improvements to Panasonic's unique SOLID SHINE Laser cooling system achieve 20,000 hours*2 of maintenance-free operation, all from the same compact body-size as our 1-Chip DLP™ WUXGA laser models.

*1 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2012 international standards. Value is average of all products when shipped. *2 At this time, brightness will have decreased to approximately 50 % of its original level (Dynamic Contrast Mode [ON]). Panasonic recommends cleaning or checkup at point of purchase after about 20,000 hours. Light-source lifetime may be reduced depending on environmental conditions. Replacement of parts other than the light source may be required in a shorter period.

Specifications (Tentative)

Model	With supplied lens	PT-RCQ10	PT-RCQ80
	Without lens	PT-RCQ10L	PT-RCQ80L
Projector type		1-Chip DLP™ projector	
DLP™ chip	Panel size	17.0 mm (0.67 in) diagonal, 16:10 aspect ratio	
	Display method	DLP™ chip x 1, DLP™ projection system	
	Number of pixels	2,304,000 (1920 × 1200) pixels	
Light source		Laser diodes	
Light output*1		10,000 lm	8,000 lm
Time until light output declines to 50 %*2		20,000 hours (NORMAL) / 24,000 hours (ECO)	
Resolution		4,608,000 pixels / 2715 x 1697 dots * With Smooth Pixel Drive: ON.	
Contrast ratio*1		10,000:1 (Full On/Full Off, Dynamic Contrast Mode: ON)	
Screen size [diagonal]		1.27–15.24 m (50–600 in), 1.27–5.08 m (50–200 in) with ET-DLE055, 2.54–8.89 m (100–350 in) with ET-DLE035, 2.54–10.16 m (100–400 in) with ET-DLE020, 16:10 aspect ratio	
Center-to-corner zone ratio*1		90 %	
Lens		PT-RCQ10: Powered zoom (throw ratio 1.71-2.41:1), F 1.7–1.9, f 25.6–35.7 mm PT-RCQ10L: Optional powered zoom/focus lenses	
		PT-RCQ80: Powered zoom (throw ratio 1.71-2.41:1), F 1.7–1.9, f 25.6–35.7 mm PT-RCQ80L: Optional powered zoom/focus lenses	
Lens shift*3	Vertical (from center of screen)	+50 %, -16 % (+40 %, -16 % with ET-DLE060) (powered)	
	Horizontal (from center of screen)	+30 %, -10 % (+10 %, -20 % with ET-DLE020, +19 %, -10 % with ET-DLE060, +28 %, -10 % with ET-DLE105/ET-DLE085) (powered)	
Keystone correction range		Vertical: ±40° (±5° with ET-DLE020, ±16° with ET-DLE060, ±22° with ET-DLE105/ET-DLE085/ET-DLE055, +5° with ET-DLE035), Horizontal: ±15° (±10° with ET-DLE060) (cannot be operated with ET-DLE035/ET-DLE020)	
Keystone correction range with optional ET-UK20 Upgrade Kit		Vertical: ±45° (±16° with ET-DLE060, ±40° with ET-DLE150/ET-DLE250/ET-DLE170, ±22° with ET-DLE105/ET-DLE085/ET-DLE055), Horizontal: ±40° (±10° with ET-DLE060, ±15° with ET-DLE105/ET-DLE085/ET-DLE055), When [VERTICAL KEYSTONE] and [HORIZONTAL KEYSTONE] are used simultaneously, correction cannot be made exceeding a total of 55°.	
Installation		Ceiling/floor, front/rear, free 360-degree installation	
Terminals	SDI IN	BNC x 1: 3G/HD-SDI input	
	HDMI IN	HDMI 19-pin x 1 (Deep Color, compatible with HDCP 2.2, 4K/60p signal input*4)	
	DVI-D IN	DVI-D 24-pin x 1 (DVI 1.0 compliant, compatible with HDCP, compatible with single link only)	
	MULTI PROJECTOR SYNC IN	BNC x 1	
	MULTI PROJECTOR SYNC OUT	BNC x 1	
	SERIAL IN	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)	
	SERIAL OUT	D-sub 9-pin (male) x 1 for link control	
	REMOTE 1 IN	M3 x 1 for wired remote control	
	REMOTE 1 OUT	M3 x 1 for link control (for wired remote control)	
	REMOTE 2 IN	D-sub 9-pin (female) x 1 for external control (parallel)	
	LAN	RJ-45 x 1 for network connection, 10Base-T/100Base-TX, compliant with PjLink™ (Class 2), Art-Net	
	DIGITAL LINK	RJ-45 x 1 for network, DIGITAL LINK connection (HDBaseT™ compliant), 100Base-TX, compatible with Art-Net, PjLink™ (Class 2), Deep Color, HDCP 2.2, 4K/60p signal input*4	
	USB	USB Connector (Type A) x 1 for Cloning/Wireless Module (output 5 V/500 mA)	
	Expansion Slot	SLOT for interface boards, SLOT NX compatible	
	Power supply		AC 100–240 V, 50/60 Hz
Power consumption		1,100 W	880 W
Cabinet materials		Molded plastic	
Operation noise*1		43 dB (Normal)/40 dB (Quiet 1)/38 dB (Quiet 2)	40 dB (Normal)/38 dB (Quiet 1)
Dimensions (W × H × D)		PT-RCQ10: 498 x 200*5 x 581 mm (19 19/32" x 7 7/8" x 22 7/8") (with supplied lens)	PT-RCQ80: 498 x 200*5 x 581 mm (19 19/32" x 7 7/8" x 22 7/8") (with supplied lens)
		PT-RCQ10L: 498 x 200*5 x 538 mm (19 19/32" x 7 7/8" x 21 3/16") (without lens)	PT-RCQ80L: 498 x 200*5 x 538 mm (19 19/32" x 7 7/8" x 21 3/16") (without lens)
Weight*5		PT-RCQ10: 24.2 kg (53.4 lbs) (with supplied lens)	PT-RCQ80: 24.2 kg (53.4 lbs) (with supplied lens)
		PT-RCQ10L: 23.4 kg (51.6 lbs) (without lens)	PT-RCQ80L: 23.4 kg (51.6 lbs) (without lens)
Operating environment		Operating temperature: 0–45 °C (32–113 °F)*1, operating humidity: 10–80 % (no condensation)	
Applicable software		Logo Transfer Software, Multi Monitoring & Control Software, Geometry Manager Pro, Smart Projector Control for iOS/Android™	

*1 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2012 international standards. Value is average of all products when shipped. *2 Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast contents, NORMAL Mode, Dynamic Contrast [ON], under conditions with 35 °C (95 °F), 700 m (2,297 ft) above sea level, and 0.15 mg/m³ of particulate matter. Estimated time until light output declines to 50 % varies depending on environment. *3 Lens shift is not supported on the ET-DLE055, and the optical axis is fixed with the ET-DLE035. *4 4K input signal is converted to 2715 x 1697 dots. *5 With legs at shortest position. *6 Average value. May differ depending on the actual unit. *7 When using the projector at an altitude lower than 2,700 m (8,858 ft) above sea level, and the operating environment temperature becomes 30 °C (86 °F) or higher, the light output may be reduced to protect the projector. When using the projector at an altitude between 2,700 m (8,858 ft) and 4,200 m (13,780 ft), and the operating environment temperature becomes 25 °C (77 °F) or higher, the light output may be reduced to protect the projector.

Optional Accessories

- **Fixed-Focus Lens**
ET-DLE035 (0.380:1) / ET-DLE055 (0.785:1)
- **Zoom Lens**
ET-DLE020* (0.280-0.299:1) / ET-DLE060 (0.600-0.801:1) / ET-DLE085 (0.782-0.977:1) / ET-DLE105 (0.978-1.32:1) / ET-DLE150 (1.30-1.89:1) / ET-DLE170** (1.71-2.41:1) / ET-DLE250 (2.27-3.62:1) / ET-DLE350 (3.58-5.45:1) / ET-DLE450 (5.36-8.58:1)
* Available from October 2019.
** US/Europe only. ET-DLE170 is equivalent of supplied lens.
Note: With WUXGA resolution. Value depends on resolution.
- **Ceiling Mount Bracket**
ET-PKD130H (6-axis, for high ceiling)
ET-PKD120H (for high ceiling)
ET-PKD120S (for low ceiling)
- **Projector Mount Bracket**
ET-PKD130B
- **Interface Board for 12G-SDI Input**
ET-MDN12G10
- **Interface Board for HDMI® (HDCP 2.2) Input**
ET-MDNHM10
- **Interface Board for DVI Input**
ET-MDNDV10
- **Interface Board for DisplayPort™**
ET-MDNDP10
- **Wireless Module**
AJ-WM50
Note: Product availability may vary by country or region. The suffix at the end of the model number is omitted.
- **DIGITAL LINK Switcher**
ET-YFB200G
Note: ET-YFB200G is not compatible with 4K signals.
- **Digital Interface Box**
ET-YFB100G
Note: ET-YFB100G is not compatible with 4K signals.
- **Geometry Manager Pro Software Upgrade Kit**
ET-UK20
- **Auto Screen Adjustment Upgrade Kit**
ET-CUK10/ET-CUK10P
- **Early Warning Software**
ET-SWA100 Series
Note: Part number suffix may differ depending on the license type.
* Multi Monitoring & Control Software Ver. 2.0 or later is required. Please download from the following website:
<https://panasonic.net/cns/projector/download/application/>



Weights and dimensions shown are approximate. Specifications and appearance are subject to change without notice. Product availability may vary by country or region. This product may be subject to export control regulations. DLP, DLP logo and DLP Medallion logo are trademarks or registered trademarks of Texas Instruments. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries. Trademark PjLink is a trademark applied for trademark rights in Japan, the United States of America and other countries and areas. Android is a trademark or registered trademark of Google LLC. IOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license. SOLID SHINE is a trademark of Panasonic Corporation. All other trademarks are the property of their respective trademark owners. © 2019 Panasonic Corporation. All rights reserved.



For more information about Panasonic projectors, please visit:
Projector Global Website – panasonic.net/cns/projector
Facebook – www.facebook.com/panasonicprojectoranddisplay
YouTube – www.youtube.com/user/PanasonicProjector