

VS-84HN

8x4 HDMI Matrix Switcher















The VS-84HN is a high-performance matrix switcher for HDMI signals. It reclocks and equalizes the signal and can route any input to any or all outputs simultaneously.

FEATURES

- Max. Data Rate 6.75Gbps (2.25Gbps per graphic channel).
- HDTV Compatible.
- HDCP Compliant.
- HDMI Support Deep Color, x.v.Color™, Dolby® TrueHD, Dolby Digital Plus, DTS-HD®, and linear PCM 7.1 surround sound.
- 3D Pass-Through.
- Kramer Equalization & re-Klocking™ Technology Rebuilds the digital signal to travel longer distances.
- EDID Capture Copies and stores the EDID from a display device.
- Output Disconnect Each output.
- Front Panel Control Lockout.
- Memory Locations Stores multiple switches as presets to be recalled and executed when needed.
- Flexible Control Options Front panel, IR remote, RS-232 (K-Router Plus™ Windows®-based software is included), Ethernet (Windows®-based Ethernet Configuration Manager & Virtual Serial Port Manager is included).
- Worldwide Power Supply 100-240V AC.
- Standard 19" Rack Mount Size 1U. Rack "ears" included.

TECHNICAL SPECIFICATIONS

INPUTS: 8 HDMI connectors.

OUTPUTS: 4 HDMI connectors.

MAX. DATA RATE: 6.75Gbps (2.25Gbps per graphic channel).

COMPLIANCE WITH HDMI STANDARD: HDMI and HDCP.
RESOLUTION: Up to UXGA; 1080p.

POWER CONSUMPTION: 100-240V AC, 50/60Hz, 40VA.

CONTROLS: Front panel buttons, infrared remote control transmitter, RS-232, Ethernet.

OPERATING TEMPERATURE: 0° to +40°C (32° to 104°F).

STORAGE TEMPERATURE: -40° to +70°C (-40° to 158°F).

HUMIDITY: 10% to 90%, RHL non-condensing.

INCLUDED ACCESSORIES: Power cord, IR transmitter, rack "ears".

PRODUCT DIMENSIONS: 19" x 9.34 x 1U (43.6cm x 23.72cm 4.36cm) W, D, H

PRODUCT WEIGHT: 1.7kg (3.6lbs) approx.

SHIPPING DIMENSIONS: 52.50cm x 33.00cm x 10.70cm (20.67" x 12.99" x 4.21") W, D, H

SHIPPING WEIGHT: 2.3kg (5.1lbs) approx.

