



PT-120

Computer Graphics Video over Twisted Pair Receiver



Compatible with HDTV component video signals when used with a breakout cable such as the Kramer C-GM/3RVF.



The PT-120 is a twisted pair receiver for computer graphics video signals. It converts a twisted pair signal from a PT-110 transmitter (or other compatible Kramer transmitter) to a computer graphics signal.

FEATURES

- HDTV Compatible.
- Max. Resolution - WUXGA & 1080p.
- Level (Gain) & EQ (Peaking) Controls.
- System Range - Up to 100m (320ft). Greater distances possible depending on signal resolution and cable.
- Cable - UTP (unshielded twisted pair) or STP (shielded twisted pair) cable such as CAT 5.
- Power Connect™ System - A single connection to the transmitter or the receiver powers both units when the devices are within 150ft (50m) of each other.
- Ultra Compact Pico TOOLS™ - 4 units can be rack mounted side-by-side in a 1U rack space with the optional RK-4PT rack adapter.

TECHNICAL SPECIFICATIONS

INPUT:	1 twisted pair on an RJ-45 connector.
OUTPUT:	1 VGA/UXGA on a 15-pin HD connector.
MAX. OUTPUT LEVEL:	1.5Vpp.
MAX. RESOLUTION:	WUXGA & 1080p.
DIFF. GAIN:	2.9% (worst case).
DIFF. PHASE:	0.3Deg (worst case).
K-FACTOR:	<0.05%.
S/N RATIO:	69dB (worst case).
CONTROLS:	-7.7dB to +3.1dB, 130m (level); 0dB to +25dB, (EQ.) @50MHz.
COUPLING:	DC.
POWER CONSUMPTION:	12V DC, 175mA.
INCLUDED ACCESSORIES:	Power supply.
OPTIONS:	RK-4PT 19" rack adapter.
PRODUCT DIMENSIONS:	6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96") W, D, H
PRODUCT WEIGHT:	0.1kg (0.2lbs) approx.
SHIPPING DIMENSIONS:	0.00cm x 0.00cm x 0.00cm (0.00" x 0.00" x 0.00") W, D, H
SHIPPING WEIGHT:	0.6kg (1.3lbs) approx.

